

# Disc harrows ART (Combined and articulated lance)




## Standard equipment:

- › Separation between AR-25 discs: 25 cm.
- › Models with 250x100x8 mm rectangular tubular rectangular chassis.
- › Hydraulic control for the activation of the opening or closing of the harrow, pneumatic wheel equipment or lance.
- › Filming system provided with MONOBLOC self-aligning housings of ball bearings protected with triple seals that SIMPLIFY THE NEED FOR LUBRICATION.
- › Solid steel frame shaft (F-114) 40x40 mm for all models
- › Standard simple discs. **(26" discs as standard in 6 mm and 28" as standard in 7 mm of thickness.)**


CODE	MODEL	DISCS				TIRES	WIDTH (m)		WEIGHT (Kg)	POWER (CV)
		Núm.	Supports	Diameter	Separation		Work	Transport		
1011070015	ART-25-40-26	40	16	26" - 66	250 mm.	11.5/80-15.3" (14PR)	5	2,85	4.275	200-220
1011070016	ART-25-40-28	40	16	28" - 71	250 mm.	11.5/80-15.3" (14PR)	5	2,85	4.570	200-220
1011070017	ART-25-44-26	44	16	26" - 66	250 mm.	11.5/80-15.3" (14PR)	5,5	2,85	4.430	220-240
1011070018	ART-25-44-28	44	16	28" - 71	250 mm.	11.5/80-15.3" (14PR)	5,5	2,85	4.750	220-240
1011070019	ART-25-48-26	48	16	26" - 66	250 mm.	11.5/80-15.3" (14PR)	6	2,85	4.830	240-260
1011070020	ART-25-48-28	48	16	28" - 71	250 mm.	11.5/80-15.3" (14PR)	6	2,85	5.185	240-260
1011070021	ART-25-52-26	52	16	26" - 66	250 mm.	11.5/80-15.3" (14PR)	6,5	2,85	4.920	260-280
1011070022	ART-25-52-28	52	16	28" - 71	250 mm.	11.5/80-15.3" (14PR)	6,5	2,85	5.300	260-280

## Options




**Fixed hydraulic shot increase**

CODE  
2011070001




**Additional support point increase (price per unit):**

CODE  
2019020004




**28" disc increment in 8 mm (price per unit):**

CODE  
2019020001




**280 mm disc separation increment (price per unit):**

CODE  
2019020002



**Bearing housing protector (price per unit):**

CODE  
2019020003



**Increase pneumatic wheels**  
400/60-15.5" (14PR)  
34 to 36 discs

CODE  
2011070003