

Disc harrows SH-PH (Central wheels). Hydraulic folding



CODE	MODEL	DISCS				TIRES	WIDTH (m)		WEIGHT (Kg)	POWER (CV)
		Núm.	Supports	Diameter	Separation		Work	Transport		
1011080001	SH PH-25-24-26	24	8	26" - 66	250 mm.	400/60-15.5"(14PR)	3	2,6	2.630	110-120
1011080002	SH PH-25-24-28	24	8	28" - 71	250 mm.	400/60-15.5"(14PR)	3	2,6	2.700	110-120
1011080003	SH PH-25-26-26	26	8	26" - 66	250 mm.	400/60-15.5"(14PR)	3,25	2,6	2.920	120-130
1011080004	SH PH-25-26-28	26	8	28" - 71	250 mm.	400/60-15.5"(14PR)	3,25	2,6	2.995	120-130
1011080005	SH PH-25-28-26	28	8	26" - 66	250 mm.	400/60-15.5"(14PR)	3,5	2,6	3.290	130-140
1011080006	SH PH-25-28-28	28	8	28" - 71	250 mm.	400/60-15.5"(14PR)	3,5	2,6	3.460	130-140
1011080007	SH PH-25-32-26	32	8	26" - 66	250 mm.	400/60-15.5"(14PR)	4	2,6	3.440	140-160
1011080008	SH PH-25-32-28	32	8	28" - 71	250 mm.	400/60-15.5"(14PR)	4	2,6	3.660	140-160
1011080009	SH PH-25-36-26	36	12	26" - 66	250 mm.	400/60-15.5"(14PR)	4,5	2,6	3.900	160-170
1011080010	SH PH-25-36-28	36	12	28" - 71	250 mm.	400/60-15.5"(14PR)	4,5	2,6	4.100	160-170
1011080011	SH PH-25-40-26	40	16	26" - 66	250 mm.	400/60-15.5"(14PR)	5	2,6	4.350	180-190
1011080012	SH PH-25-40-28	40	16	28" - 71	250 mm.	400/60-15.5"(14PR)	5	2,6	4.550	180-190

Standard equipment:

- › Separation between SH-25 discs: 25 cm.
- › Models with rectangular tubular chassis suspended 160x80x8 mm.
- › 250x100x8 mm disc carrier chassis.
- › Eccentric shot.
- › Hydraulic control for the activation of the opening or closing of the harrow or the pneumatic wheel unit or the lance.
- › Filming system provided with MONOBLOC self-aligning housings of ball bearings protected with triple seals
- › sealed that SIMPLIFY THE NEED FOR LUBRICATION. Solid steel frame shaft (F-114) 40x40 mm for all models.
- › Standard simple discs. (26" discs as standard in 6 mm and 28" as standard in 7 mm of thickness.).



Options



Hydraulic adjustment of cloth level

CODE
2011080001



Hydropneumatic damping

CODE
2011080002




Hydraulic Spear Shifter

CODE
2011080003




Additional support point increase (price per unit):

CODE
2019020004



28" disc increment in 8 mm (price per unit):

CODE
2019020001



280 mm disc separation increment (price per unit):

CODE
2019020002



Bearing housing protector (price per unit):




CODE
2019020003



500 / 50-17 wheel increment (14 PR)

CODE
2011080005

Rollers



FOR MODEL:	Cage roller Ø 400 mm. 10 rows - 25 mm			Cage roller Ø 550 mm. 9 Rows - 25 mm			Cage roller Ø 550 mm - 10 Wavy bars 60x8 mm		
	CODE	Width (m)	Kg	CODE	Width (m)	Kg	CODE	Width (m)	Kg
SH PH-25-24	2011080008	3,3	420	2011080016	3,3	490	2011080024	3,3	490
SH PH-25-26	2011080009	3,55	470	2011080017	3,55	550	2011080025	3,55	550
SH PH-25-28	2011080010	3,8	540	2011080018	3,8	630	2011080026	3,8	630
SH PH-25-32	2011080011	4,3	610	2011080019	4,3	710	2011080027	4,3	710
SH PH-25-36	2011080012	4,8	680	2011080020	4,8	790	2011080028	4,8	790
SH PH-25-40	2011080013	5,3	760	2011080021	5,3	870	2011080029	5,3	870

