

Discs harrows SR-25 (Rear wheels)

Standard equipment:

- › Separation between SR-25 discs: 25 cm.
- › Models with 250x100x8 mm rectangular tubular chassis.
- › Eccentric shot.
- › Hydraulic system for actuating the opening or closing of the stands and the rear wheel pneumatic equipment.
- › Filming system provided with MONOBLOC self-aligning housings of ball bearings protected with triple-sealed seals that SIMPLIFY THE NEED FOR LUBRICATION.
- › Solid steel frame shaft (F-114) 40x40 mm for all models.
- › Standard simple discs.



CODE	MODEL	DISCS				TIRES	WIDTH (m)		WEIGHT (Kg)	POWER (CV)
		Núm.	Supports	Diameter	Separation		Work	Transport		
1011060013	SR-25-16-26	16	4	26" - 66	250 mm.	10.0/80-12" (8PR)	1,91	2,1	1.140	65-70
1011060014	SR-25-16-28	16	4	28" - 71	250 mm.	10.0/80-12" (8PR)	1,91	2,1	1.225	65-70
1011060015	SR-25-18-26	18	6	26" - 66	250 mm.	10.0/80-12" (8PR)	2,16	2,35	1.210	70-75
1011060016	SR-25-18-28	18	6	28" - 71	250 mm.	10.0/80-12" (8PR)	2,16	2,35	1.305	70-75
1011060017	SR-25-20-26	20	8	26" - 66	250 mm.	10.0/80-12" (8PR)	2,41	2,6	1.275	75-80
1011060018	SR-25-20-28	20	8	28" - 71	250 mm.	10.0/80-12" (8PR)	2,41	2,6	1.380	75-80
1011060019	SR-25-22-26	22	8	26" - 66	250 mm.	10.0/80-12" (8PR)	2,66	2,85	1.520	80-85
1011060020	SR-25-22-28	22	8	28" - 71	251 mm.	10.0/80-12" (8PR)	2,66	2,85	1.635	80-85

Options



Additional support point increase (price per unit):

CODE

2019020004



28" disc increment in 8 mm (price per unit):

CODE

2019020001



280 mm disc separation increment (price per unit):

CODE

2019020002



Bearing housing protector (price per unit):

CODE

2019020003



Increase pneumatic wheel (10,0/75-15,3")

CODE

2011060001

